IN THE CLAIMS:

Please amend the claims as indicated in the claim listing that follows. The following claim listing will replace all prior claim listings.

- 1. (Canceled)
- 5
- 2. (Canceled)
- 3. (*Currently Amended*) The flocculant mentioned in Claim [[2]] <u>17</u> wherein the above-mentioned alkaline substance is calcium carbonate or lime.

10

- 4. (*Previously Amended*) The flocculant mentioned in Claim 3 wherein said acid solvent is diluted hydrochloric acid.
- 5. (Currently Amended) The flocculant mentioned in Claim 4, wherein said acid solvent contains one, two, or more gelation suppressant suppressants selected from an acetic acid, ammonium acetate, and ammonium chloride group.
 - 6. (*Previously Presented*) The flocculant mentioned in Claim 5, wherein said silicon-containing substance contains iron or aluminum.

20

- 7. (Currently Amended) The flocculant mentioned in Claim 6, wherein the having a pH value is of 2 to 3.
 - 8. (Currently Amended) A manufacturing method for a flocculant made

5

10

15

from a silicon-containing substance generation means for mixing comprising the steps of: combining a silicon-containing substance and an alkaline substance; and heat treating the result resulting combination at a temperature lower than the melting temperature of said silicon-containing substance to generate an acid soluble silicon-containing substance; [[,]] combining the acid soluble silicon-containing substance with an acid solvent to obtain an acid solvent generation means for generating a solvent made from an acid solvent in said silicon-containing substance to generate a acid silicon colloidal solution that is a flocculant.

- 9. (Original) The manufacturing method for a flocculant mentioned in Claim 8 wherein said alkaline substance is made from calcium carbonate or lime.
- 10. (Currently Amended) The manufacturing method for a flocculant mentioned in Claim 9, wherein said acid solvent generation means comprises a means for diluting diluted hydrochloric acid to generate an acid solvent.
- 11. (Previously Presented) The manufacturing method for a flocculant mentioned in Claim 10, wherein said acid solvent generation means includes means for mixing one, two, or more gelation suppressants selected from said an acetic acid, ammonium acetate, and ammonium chloride with said acid solution.
- 12. (Currently Amended) The manufacturing method for a flocculant mentioned in Claim 11, further comprising the step of passing the acid silicon

colloidal solution through a filter wherein a filtering means is added for filtering said silicon colloidal solution to remove undissolved suspended matter.

- 13. (*Previously Presented*) The manufacturing method for a flocculant mentioned in Claim 12, wherein an aggregating means is added for adding gypsum to said silicon colloidal solution to cause undissolved suspended matter to aggregate.
- 14. (*Previously Presented*) The manufacturing method for a flocculant mentioned in Claim 13, wherein a pH adjustment means is added to add iron or aluminum to said silicon colloidal solution to adjust the pH value of said silicon colloidal solution.
- 15. (*Previously Presented*) A flocculation method for mixing the flocculant mentioned in Claim 7 with a suspension to flocculate suspended matter.
 - 16. (*Original*) The flocculation method mentioned in Claim 15, wherein a means is added for further mixing an alkaline substance in a suspension.

20

5

Docket No. F-8960

17. (New) A flocculant for flocculating suspended matter, the flocculant obtainable by dilution of a silicon collodial solution, wherein the flocullant is obtained by:

5

10

mixing a silicon-containing substance with an alkaline substance, heating the resulting mixture at a temperature below the melting point of the silicon-containing substance, whereby the silicon-containing substance is rendered acid soluble, and

dissolving the so-heat-treated silicon-containing substance in an acid solvent to obtain the flocculant.